

# Eaton 5P1500

Catalog Number: 5P1500

Eaton 5P UPS, Tower, 1440 VA, 1100 W, 5-15P input, Outputs: (8) 5-15R, 120V, true sine wave, network card optional



## General specifications

Product Name	Catalog Number
Eaton 5P UPS	5P1500
UPC	Product Length/Depth
743172043009	17.5 in
Product Height	Product Width
9.1 in	5.9 in
Product Weight	Compliances
35.6 lb	CE Marked
	RoHS Compliant

## Certifications

cULus Listed  
UL 1778  
UL 497A  
IEC 62040-2 C1-C2 / EN 55024 /  
CISPR22 Class B / FCC part 15 Class B

## Especificaciones del producto

### Special features

ROO/RPO: Rear terminal block connector for remote on/off and power off

### Topology

Line-interactive

### Form factor

Tower

### Color

Black/silver

### VA rating

1440 VA

### Wattage

1100 W

### Package contents

- 5P UPS
- User manual CD
- Intelligent Power Software Suite CD
- Quick start guide
- USB cable
- RS-232 serial cable

### Input connection

5-15P

### Input cord length

6 ft

### Input nominal voltage

120V default (100/110/120/127V)

### Nominal frequency

50-60 Hz

### Input frequency range

47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40-70 Hz in low-sensitivity mode

### Input power factor

0.77

### Receptacle

(8) 5-15R

## Recursos

[Guías de especificaciones de producto](#)

[Manuales y guías de uso](#)

## Output waveform

Sine wave

## Voltage

120V

## Output nominal voltage

120V default (100/120/125V)

## Feed type

1

## Runtime graph

\$row.attributeValue.cdata

## Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

## Battery replacement

User replaceable

## Battery type

Sealed, lead-acid

## Extended battery capability

None; See Eaton 5PX UPS for extended runtimes options

## Standard factory warranty

3-YEAR FACTORY

WARRANTY w/

REGISTRATION

-3 years

-Parts, electronics, and

batteries coverage

-Standard ground shipping

-Technical support

## Extended service plans

ADVANCED DEPOT

EXCHANGE

-5-YEAR DEPOT REPAIR:

5SW5Y-1750UC

-Expedited parts coverage

for 5 years

-Parts, electronics and UPS

batteries coverage

-Next business day shipping

-Technical support

5-YEAR ON-SITE PLAN:

WFLN75XX-2509UC

- On-site parts and labor coverage for years 5
- Parts, electronics and UPS batteries coverage
- 24x7 on-site labor coverage, next-day response
- Next-day shipping
- Technical support

#### Communication

RS-232 (RJ45) ports; USB port as standard (HID). 6-foot RS-232 and USB cables included

#### Expansion slots

One slot; Gigabit Network Card (Network-M2) is optional

#### Software compatibility

Eaton Intelligent Power Manager

#### User interface

LCD graphical display

#### Altitude

Up to 10,000 ft (3000m) without de-rating

#### BTU Rating

Online: 113, Battery 714

#### Noise level

<45 dB at 1 meter

#### Relative humidity

0-90% non-condensing

#### Temperature range

0° to 40°C (32° to 104°F)

#### Efficiency

97%

#### Input voltage range

89-151 Vac (adjustable to 70-153 Vac)

#### Output power factor

0.76

#### Output voltage range

102-132 Vac

#### Quantity

1



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. Todos los  
derechos reservados.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)